











High Humidity & Heat Resistant LED Lighting








- AC LED Driver-less Technology
- Intended for Use in High Ambient Temperature Environments

	L1203 <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	COB	20W	120V, 220V, 277V, 480V
	P1202 <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	COB	40W	120V, 220V, 277V, 480V
	L1105 <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	COB	40W	120V, 220V, 277V, 480V
			60W	120V, 220V, 277V, 480V
	L1705A <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	COB	20W	120V, 277V
	L1705C <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	COB	40W	120V, 277V
			50W	120V, 277V
	L1102 <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	COB	60W	120V, 208V, 220V, 277V, 480V
			80W	120V, 208V, 220V, 277V
	L1319 2ft <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	SMD	40W	120V, 220V, 277V
			60W	220V
	L1319C 2ft <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	SMD	40W	120V, 220V, 277V
			60W	120V, 220V, 277V

High Humidity & Heat Resistant LED Lighting



- AC LED Driver-less Technology
- Intended for Use in High Ambient Temperature Environments

	L1319C 4ft <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	SMD	40W	120V, 220V, 277V
			80W	120V, 220V, 277V, 347V, 480V
	L1219A	COB	20W	220V
	L1219B	COB	50W	110V, 220V
			60W	110V, 220V
	L1219C	COB	40W	110V, 220V
			50W	110V, 220V
			60W	110V, 220V
	L1217 <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	COB	120W	120V, 220V, 277V, 480V
	L1733N <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	COB	120W	120V, 277V, 347V, 480V

***85°C to 65°C – 2 years warranty without warranting lumen depreciation.**










Safety is Your Top Priority!

High Humidity & Heat Resistant LED Lighting



- AC LED Driver-less Technology
- Intended for Use in High Ambient Temperature Environments

	L1512D <small>UL 1598 Luminaires CSA C22.2 No.250.0</small>	COB	140W	120V, 277V, 347V, 480V
			160W	120V, 277V, 347V, 480V
	W1319C 2ft	COB	60W	120V, 220V, 277V
			80W	120V, 220V, 277V
	W1319C 4ft	COB	80W	120V, 220V, 277V
			120W	120V, 220V, 277V
			240W*	120V, 220V, 277V
*Only for 70°C Heat Resistant				
Clear PC Cover  Matte PC Cover   Red  Green	W1905	COB	20W-Red	120V, 220V, 277V, 347V, 480V
			20W-Green	120V, 277V, 480V
			30W	100V, 110V, 120V, 200V, 208V, 220V, 230V, 240V, 277V, 347V, 480V
		SMD	50W-Red	220V
			40W	110V, 120V, 220V, 230V, 277V, 347V, 480V
			50W	110V, 120V, 220V, 230V, 277V, 347V, 480V
			60W	110V, 120V, 220V, 230V, 277V, 347V, 480V

***85°C to 65°C – 2 years warranty without warranting lumen depreciation.**