

00-IC-F0056-1 - Issue 17.0

[15]

# Schedule EU-TYPE EXAMINATION CERTIFICATE No. DEMKO 16 ATEX 1623X Rev. 1

## Description of Product

The Model L1319 series of luminaires is suitable for use in hazardous location classified as Zone 1, Zone 2, Zone 21 and Zone 22. This luminaire consists of three interconnecting "db"/"tb" chambers: one is the top cover for wiring connection to cable gland, the others are the LED array chambers. The enclosure material is aluminum alloy. The light-transmitting parts are made of tempered flat glass. The gasket is used to maintain the IP rating. The entry for wiring through integral cable gland maintains the degree of protection. Unused entries are fitted with blanking elements to maintain the degree of protection.

#### Nomenclature for Luminaires:

The complete luminaire catalog number example is as follows:

	Cat.	THT	E	1319	Z	С	С	С	2	D0	-S25
No. 1 2 3 4 5 6 7 8 9	No.	1	2	3	4	5	6	7	8	9	10

- 1 Brand name, THT = Top Hi-Tech Co., Ltd.
- 2 Category of product, E = Explosion proof lighting fixtures
- 3 Model name, 1319 = Model 1319 series
- 4 Sub-series designation, Z = No sub-series under this model
- 5 Designates type of Top Cover, C = Top Cover with opening
- 6 Designates type of LED module, C = LED bar; H = SMD type
- 7 Designates CCT of LED, C = Cool white; W = Warm white
- 8 Designates voltage, 2 = 220 Vac; 1 = 110 Vac
- 9 Designates wattage of LED lighting, D0 = 40 W
- 10 Mounting type, W90 = Wall mounting; H90 = Hanging mounting; C90 = Ceiling mounting; S25 = Stanchion mounting 25°, P90 = Pendant mounting

#### Models covered are as follows:

Model	Ambient Temperature range	Gas Temperature Code	Dust Temperature Rating
THTE1319ZC**2D0-***	-40℃ to +55℃	Т6	Τ85℃
THTE1319ZC**1D0-***	-40℃ to +55℃	Т6	T85℃

The optical radiation output of the product with respect to explosion protection, according to Annex II clause 1.3.1 of the Directive 2014/34/EU is not covered in this certificate.

#### Temperature range

The ambient temperature range is -40°C to +50°C.

#### Electrical data

THTE1319ZC\*\*2D0-\*\*\* series – 220 Vac, 50/60 Hz, 40 W THTE1319ZC\*\*1D0-\*\*\* series – 110 Vac, 50/60 Hz, 40 W

#### Routine tests

Routine overpressure tests in accordance with EN60079-1:2014 shall be conducted on all units in accordance with clause 15.2.3.2, at a pressure of 20.52 bar for a duration of not less than 10 seconds. There shall be no sign of damage, deformation or rupture that will invalidate the concept of protection.

## [16] Descriptive Documents

The scheduled drawings are listed in the report no. provided under item no. [8] on page 1 of this EU-Type Examination Certificate.

# [17] Specific conditions of use:

[18]

The flameproof joints are not intended to be disassembled or repaired.

## Essential Health and Safety Requirements

The Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9.

THT-E

#### Additional information

The THT-L1319 series has in addition passed the tests for Ingress Protection to IP 67 in accordance with EN60529:1991+A1:2000+A2:2013.

THT-EX The trademark

will be used as the company identifier on the marking label.

The manufacturer shall inform the notified body concerning all modifications to the technical documentation as described in Annex III to Directive 2014/34/EU of the European Parliament and the Council of 26 February 2014.